






















VITA Vollkeramik Indikationsübersicht

	Oxidkeramik					Feinstruktur-Feldspatkeramik		Machinable Polymers	
	Infiltrationskeramik			Sinterkeramik		VITABLOCS Mark II	VITABLOCS TriLuxe/TriLuxe forte	VITA CAD-Temp	VITA CAD-Waxx
	VITA In-Ceram SPINELL	VITA In-Ceram ALUMINA	VITA In-Ceram ZIRCONIA	VITA In-Ceram AL	VITA In-Ceram YZ				
 ¹⁾	—	—	—	—	—	—	—	●	●
	—	—	—	●	●	—	—	—	—
	○	—	—	—	—	●	○	—	▲
	○	—	—	—	—	●	●	—	▲
	—	—	—	—	—	●	●	—	▲
	—	—	—	—	—	●	●	—	▲
	●	● ²⁾	○	●	●	●	●	●	▲
	—	●	●	●	●	—	—	●	▲
 *	—	—	—	—	●	—	—	●	▲
	○	● ²⁾	●	●	●	●	●	●	▲
	—	—	●	—	●	—	—	●	▲
 *	—	—	—	—	●	—	—	●	▲
Verblendmaterial					 	 **	 **	 **	—

● empfohlen ○ möglich ¹⁾Bohrschablonen * maximal 2 Zwischenglieder ** nur zur Individualisierung ▲ nur als Modellierwachsersatz
²⁾sprint Technik